







# COMPUTADATA PRESENTS THE TULIP SYSTEM PC COMPACT

*4900 incl.  
+ monitor  
#5 weken levertyd.*

## MAIN UNIT — PC-BOARD

Micro processor	Intel 8088
	Clock 8 MHz
Memory	256 Kb
Display	
· Monochrome graphic adapter	Format: 80 characters/25 lines Attributes: Highlighting Blinking Reverse video Underlining
· Graphic Format	720 * 348
· Color graphic adapter	Format: 40/80 characters/25 lines Attributes: 8 colors 32 background colors Highlighting Blinking
· Graphic format	320/640 * 200 (color) 640 * 200/400 (monochrome)
Interfaces	<ul style="list-style-type: none"> <li>· Keyboard</li> <li>· Parallel I/O (Centronics compatible)</li> <li>· Serial I/O (RS 232 compatible) Software selectable baudrates 50-19200</li> <li>· Floppy disk controller</li> <li>· Expansion bus with 4 slots</li> <li>· Piggy-backed expansion slots for e.g. display adapters, L.A.N. boards and communications boards</li> </ul>
Monitor Eprom	· 16 Kb with programmable hardware checks auto OS booting, L.A.N. workstation start up and testing facilities

## MAIN UNIT — EXTERNAL MEMORY

Floppy disk drives	40 track
· number of drives	2 * 5 1/4"
· total capacity	2 * 360 Kb
· access time (average)	103 msec
· track density	48 tpi

Hard disk drives	
· number of drives	1
· capacity (formatted)	10.27 Mb
· access time (average)	155 msec

## MAIN UNIT — KEYBOARD

· Number of keys	88, compatible IBM
· Function keys	40, with special calculator-emulation key

## SOFTWARE

· Standard operating system	MS-DOS 3.1
· Standard interpreter	MicroSoft GWBASIC
· MS-WINDOWS	Paint and Write

## OPTIONS

· Hardware	<ul style="list-style-type: none"> <li>· Memory expansion upto 512 Kb</li> <li>· Intel 8087 8 MHz arithmetic co-processor</li> <li>· Two channel communication board</li> <li>· The IBM compatible expansion bus permits a wide range of options with expansion cards</li> <li>· MOUSE via serial interface</li> </ul>
· Software	<ul style="list-style-type: none"> <li>· COMPUTADATA Local Area Network (CD LAN)</li> <li>· MS-NET</li> <li>· the IBM compatibility guarantees the availability of a wide range of communication and application packages</li> <li>· MicroSoft BASIC 86 (MBASIC)</li> </ul>

## POWER SUPPLY

220 Volt/50 Hz
110 Volt/60 Hz
max 150 Watt

## ENVIRONMENTAL REQUIREMENTS

Temperatures	5 - 35° Celsius
Humidity	40 - 80 % (non condensing)

## GENERAL SPECIFICATIONS

Weight	10 kg
Dimensions	445 * 108 * 350 mm



**The Netherlands:**  
Computadata B.V. Hambakenwetering 2  
5231 DC 's-HERTOGENBOSCH Tel.: +31  
73 422045 Telex: 50316 cdata nl.

**Belgium:**  
N.V. Computadata Belgium S.A. Brussel-  
poortstraat 8, B-2800 MECHELEN Tel.:  
+32 15 422480 Telex: 64698 cdata b

**Germany:**  
Computadata Deutschland Hindenburg-  
strasse 23, 4300 ESSEN 1 Tel.: +49  
201 227452

